

Safety Data Sheet

SDS No. 283A

Section 1 - Chemical Product and Company Identification

Product/Chemical Name: Solaris Primer

General Use: Primer

Manufacturer: Smooth-On, Inc.,

5600 Lower Macungie Rd., Macungie, PA 18062 Phone (610) 252-5800, FAX (610) 252-6200

Emergency Contact: Chem-Tel

Domestic: 800-255-3924 International: 813-248-0585

Section 2 - Hazards Identification

Classification of the substance or mixture

Flammable liquids – Category 2 Aspiration toxicity – Category 1 Skin irritation – Category 2

P273

P280

Specific target organ toxicity, single exposure: Narcotic effects – Category 3

GHS Label elements, including precautionary statements

Pictogram(s):	
Signal Word: Danger	

Pictogram(s):	/ V V	
Signal Word: Dan	iger	
Physical Hazards	H225	Highly flammable liquid and vapor
Health Hazards	H304	May be fatal if swallowed and enters airways
	H315	Causes skin irritation
	H336	May cause drowsiness or dizziness
General Precautions	P101	If medical advice is needed, have product container or label at hand.
	P102	Keep out of reach of children.
	P103	Read label before use.
Prevention Statements	P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P233	Keep container tightly closed.
	P240	Ground and bond container and receiving equipment.
	P241	Use explosion-proof electrical/ventilating/lighting equipment.
	P242	Use non-sparking tools.
	P243	Take action to prevent static discharges.
	P261	Avoid breathing dust/fume/gas/mist/vapors/spray.
	P264	Wash skin thoroughly after handling.
	P271	Use only outdoors or in a well-ventilated area.

Avoid release to the environment.

protection/face protection.

Wear protective gloves/protective clothing/eye

Response	P301 + P310	IF SWALLOWED: Immediately call a POISON
Statements		CENTER or doctor/physician.
	P302 + P352	IF ON SKIN: Wash with plenty of soap and water
	P303 + P361 +	IF ON SKIN (or hair): Take off immediately all
	P353	contaminated clothing. Rinse skin with water or shower.
	P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
	P312	Call a POISON CENTER or doctor/physician if you feel unwell.
	P331	Do NOT induce vomiting.
	P332 + P313	If skin irritation occurs: Get medical advice/attention.
	P362 + P364	Take off contaminated clothing and wash it before reuse.
	P370 + P378	In case of fire: Use Water Fog, Dry Chemical, and Carbon Dioxide Foam to extinguish.
	P391	Collect spillage.
Storage Statements	P403 + P235	Store in a well-ventilated place. Keep cool.
	P405	Store locked up.
Disposal Statements	P501	Dispose of contents/container according to local, state and federal laws.

Hazards not otherwise classified (HNOC) or not covered by GHS - none

Section 3 - Composition / Information on Ingredients

The following ingredients are hazardous according to OSHA criteria.

CAS	Component	Concentration
64741-66-8	Naphtha (Petroleum), Light Alkylate	<100%
682-01-9	Tetrapropyl orthosilicate	<10%

Section 4 - First Aid Measures

Inhalation: Remove source(s) of contamination and move victim to fresh air. If breathing has stopped, give artificial respiration, then oxygen if needed. Contact physician immediately.

Eye Contact: Flush eyes with plenty of water. If irritation persists, seek medical attention.

Skin Contact: In case of skin contact, wash thoroughly with soap and water.

Ingestion: Do not induce vomiting unless instructed by a physician. Never give anything by mouth to an unconscious person.

After first aid, get appropriate in-plant, paramedic, or community medical support.

Section 5 - Fire-Fighting Measures

Flammable Classification: Flammable

Extinguishing Media: Water Fog, Dry Chemical, and Carbon Dioxide Foam

Unusual Fire or Explosion Hazards: None known.

Fire-Fighting Instructions: Use water spray to cool fire-exposed surfaces and to protect personnel. Shut off "fuel" to fire. If a leak or spill has not ignited, use water spray to disperse the vapors. Either allow fire to burn under controlled conditions or extinguish with foam or dry chemical. Try to cover liquid spills with foam.

Further information: Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure demand or positive-pressure mode.

Section 6 - Accidental Release Measures

Spill /Leak procedures: Only properly protected personnel should remain in the spill area; dike and contain spill; absorb or scrape up excess into suitable container for disposal; wash area with dilute ammonia solution. Stop or reduce discharge if it can be done safely.

Environmental precautions: Prevent spillage from entering drains.

Section 7 - Handling and Storage

Handling Precautions: Minimize breathing of vapors and avoid prolonged or repeated contact with skin. Wear proper protective equipment. Use good general housekeeping procedures. Wash hands after use.

Storage Requirements: Keep container(s) tightly closed and properly labeled. Store in cool, dry, well ventilated place away from heat, direct sunlight, strong oxidizers and any incompatibles. Store in approved containers and protect against physical damage. Keep containers securely sealed when not in use. Indoor storage should meet OSHA standards and appropriate fire codes. Containers that have been opened must be carefully resealed to prevent leakage. Empty containers retain residue and may be dangerous. Avoid water contamination.

Section 8 - Exposure Controls / Personal Protection

Personal protective equipment selections vary based on potential exposure conditions such as applications, handling practices, concentration and ventilation. Information on the selection of protective equipment for use with this material, as provided below, is based upon intended, normal usage.

Respiratory Protection: If engineering controls do not maintain airborne contamination concentrations at a level which is adequate to protect worker health, an approved respirator may be needed. Follow OSHA respirator regulations 29 CFR 1910.134 and European Standards EN 141, 143 and 371; wear an MSHA/NIOSH or European Standards EN 141, 143 and 371 approved respirators such as a half-face filter respirator equipped with organic vapor cartridges. **Hand Protection:** Wear chemically resistant gloves are recommended. If contact with forearms is

likely wear gauntlet style gloves. **Eye Protection:** Safety glasses with side shields per OSHA eye- and face-protection regulations 29 CFR 1910.133 and European Standard EN166. Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact

lenses.

Other Protective Clothing/Equipment: Chemical/oil resistant clothing is recommended. Provide eye bath and safety shower.

Comments: Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Section 9 - Physical and Chemical Properties

Appearance : clear liquid

Odor/Threshold: mild petroleum odor

pH: N.A. (non-aqueous)

Melting Point/Freezing Point: N.A. Low/High Boiling Point: 208 °F/220 °F

Flash Point: >18°F

Evaporation Rate: (butyl acetate=1) ~3.8

Flammability: flammable

UEL/LEL: 0.9/6.3 (approximate)

Vapor Pressure: Not available Vapor Density (Air=1): ~4

Specific Gravity (H2O=1, at 4 °C): 0.8

Water Solubility: neglible

Partition coefficient: Not available

Auto-ignition temperature: Not available **Decomposition temperature:** Not available

Viscosity: <100 centipoise

% Volatile: >97%

Section 10 - Stability and Reactivity

Stability: These products are stable at room temperature in closed containers under normal

storage and handling conditions.

Polymerization: Hazardous polymerization cannot occur. **Chemical Incompatibilities:** Strong bases, and acids.

Hazardous Decomposition Products: Thermal oxidative decomposition can produce carbon

oxides and traces of incompletely burned carbon compounds.

Section 11- Toxicological Information

Skin Corrosion/Irritation: no data

Serious Eye Damage/Irritation: no data

Respiratory/Skin Sensitization: no data

Carcinogenicity: no data

Carcinogenicity: no data

Reproductive Toxicity: no data

Specific Target Organ Toxicity – Single Exposure: no data Specific Target Organ Toxicity – Repeated Exposure: no data

Aspiration Hazard: no data

Acute Toxicity: no data

Chronic Exposure: no data

Potential Health Effects - Miscellaneous: no data

Section 12 - Ecological Information

Toxicity: no data

Persistence and Degradability: no data Bioaccumulative Potential: no data

Mobility in Soil: no data

Other Adverse Effects: no data

Section 13 - Disposal Considerations

Disposal: Under RCRA it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws.

Empty containers retain product residue which may exhibit hazards of material, therefore to not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

Section 14 - Transport Information

DOT IATA IMDG

Shipping Name: Resin solution Shipping Name: Resin Shipping Name: Resin solution

 UN#: 1866
 solution
 UN#: 1866

 HC: 3 PG: II
 UN#: 1866
 HC: 3 PG: II

ERG: 128 HC: 3 PG: II Hazard Label: Flammable

Hazard Label: Flammable Hazard Label: Flammable

Section 15 - Regulatory Information

Chemical Inventories: All components of this formulation are listed in AICS, DSL, ENCS, IECSC, KECI, PICCS and TSCA.

EPCRA SECTION 302: This material contains no extremely hazardous substances.

CERCLA: This material is not subject to any special reporting under the requirements of the Comprehensive Environmental Response, Compensation and Liability Act (CERCLA). Contact local authorities to determine if other reporting requirements apply.

CWA/OPA: This product is classified as an oil under Section 311 of the Clean Air Act (40 CFR 110) and the Oil Pollution Act of 1990. Discharge or spills which produce a visible sheen on either surface water, or in waterways/sewers which lead to surface water, must be reported to the National Response Center (800-424-8802).

SARA (311/312) Reportable Hazard Categories: Fire. Immediate health.

<u>California Proposition 65</u>: This product does not intentionally contain any chemicals which have been identified by the state of California to cause cancer, birth defects or other reproductive harm.

Right-To-Know: This product does not contain any chemicals on RTK lists in the following States: IL. LA. MI 293. MN. NJ. PA or RI.

16 - Other Information

HMIS	
Н	2
F	3
R	0



NFPA

Revision: 2

Date Prepared: May 11, 2015

Glossary: ACGIH-American Conference of Governmental Industrial Hygienists; ANSI-American National Standards Institute; Canadian TDG-Canadian Transportation of Dangerous Goods; CAS-Chemical Abstract Service; Chemtrec-Chemical Transportation Emergency Center (US); CHIP-Chemical Hazard Information and Packaging; DSL-Domestic Substances List; EC-Equivalent Concentration; EH40 (UK)-HSE Guidance Note EH40 Occupational Exposure Limits; EPCRA-Emergency Planning and Community Right-To-Know Act; ESL-Effects screening levels; GHS-Globally Harmonized System of Classification and Labelling of Chemicals; HMIS-Hazardous Material Information Service; IATA-International Air Transport Association; IMDG-International Maritime Dangerous Goods Code; LC-Lethal Concentration; LD-Lethal Dose; LEL-Lower Explosion Level; NFPA-National Fire Protection Association; OEL-Occupational Exposure Limit; OSHA-Occupational Safety and Health Administration, US Dept. of Labor; PEL-Permissible Exposure Limit; SARA (Title III)-Superfund Amendments and Reauthorization Act; SARA 313-Superfund Amendments and Reauthorization Act, Section 313; SCBA-Self-Contained Breathing Apparatus; STEL-Short Term Exposure Limit; TCEQ-Texas Commission on Environmental Quality; TLV-Threshold Limit Value; TSCA-Toxic Substances Control Act Public Law 94-469; TWA-Time Weighted Value; UEL-Upper Explosion Level; US DOT-US Department of Transportation; WHMIS-Workplace Hazardous Materials Information System.

Disclaimer: The information contained in this Safety Data Sheet (SDS) is considered accurate as of the version date. However, no warranty is expressed or implied regarding the accuracy of the data. Since the use of this product is not within the control of Smooth-On Inc., it is the user's obligation to determine the suitability of the product for its intended application and assumes all risk and liability for its safe use.

This SDS is prepared to comply with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) as prescribed by the United States (US) Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200), the Canadian Workplace Hazardous Materials Information System (WHMIS), and European Union Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 (REACH).

Classifications of the chemical in accordance with 29 CFR 1910.1200, signal word, hazard and precautionary statement(s), symbol(s) and other information are based on listed concentration of each hazardous ingredient. Unlisted ingredients are not "hazardous" per the OSHA Hazard Communication Standard (29 CFR 1910.1200), WHMIS and EC No 1907/2006 and are considered trade secrets under US Federal Law (29 CFR and 40 CFR), Canadian Law (Health Canada Legislation), and European Union Directives.