

**SDS No. 644A** 

#### Section 1 - Identification

1.1 **Product Identifier:** Part A for Brush-On® 40, 50, 60; EZ-Mix® 40; Formlastic™ 48,

60; PMC® 121-30, PMC®-744, PMC®-746, PMC®-770, PMC®-790,

PMC®-844; Renew™ UR-40, UR-90; Reoflex® 20, 30, 40;

UreCoat®; Urethane 4400; Vytaflex® 10, 20, 30, 40

1.2 **General Use:** Polyurethane Elastomer

1.3 Manufacturer: Smooth-On, Inc.,

> 5600 Lower Macungie Rd., Macungie, PA 18062 Phone (610) 252-5800, sds@smooth-on.com

1.4 **Emergency Contact:** Chem-Tel Domestic: 800-255-3924 International: 813-248-0585

### Section 2 – Hazard(s) Identification

#### 2.1 Classification of the substance or mixture:

**H302** Acute toxicity, oral - Category 4

**H312** Acute toxicity, dermal - Category 4

H332 Acute toxicity, inhalation - Category 4

H315 Skin irritation - Category 2

H319 Eye irritation - Category 2A

**H335** Specific target organ toxicity-single exposure - Category 3 (respiratory)

**H351** Carcinogenicity - Category 2

#### 2.2 GHS Label elements, including precautionary statements



Pictogram(s):

Signal word: Warning

### **Health Hazards:**

H302 + H312 + H332 Harmful if swallowed, in contact with skin or if inhaled

Causes skin irritation H315

H319 Causes serious eye irritation May cause respiratory irritation H335 H351 Suspected of causing cancer.

**General Precautions:** 

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

Read label before use. P103

### **Prevention Precautions:**

P202 Do not handle until all safety precautions have been read and understood.

Avoid breathing dust/fume/gas/mist/vapors/spray. P261 P264 Wash with soap and water thoroughly after handling. P270 Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area. P271

Wear protective gloves/protective clothing/eye protection/face protection. P280

#### **Response Precautions:**

P301 + P312 IF SWALLOWED: Call a POISON CENTRE/doctor/physician if you feel

unwell.



**SDS No. 644A** 

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for

breathing.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P312 Call a POISON CENTRE/doctor/physician if you feel unwell.

P330 Rinse mouth.

P332 + P313 If skin irritation occurs: Get medical advice/attention. P337 + P313 If eye irritation persists: Get medical advice/attention.

P362 Take off contaminated clothing.

**Storage Precautions:** 

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

**Disposal Precautions:** 

P501 Dispose of contents/container according to local, state and federal laws.

Hazards not otherwise classified (HNOC) or not covered by GHS – Lachrymator.

This product contains a chemical known to be hazardous according to California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65). (See also Section 3 and 15)

### **Section 3 - Composition / Information on Ingredients**

### 3.1 Substances

The following ingredients are hazardous according to Regulation 2012 OSHA Hazard Communication Standard: 29 CFR 1910.1200:

Component	CAS#	Concentration (%wt)
Poly[oxy(methyl-1,2-ethanediyl)], α-hydro-Ω-hydroxy, polymer with 1,3 diisocyanatomethylbenzene	9057-91-4	> 80
Toluene-2,4-diisocyanate	584-84-9	< 1.0
Toluene-2,6-diisocyanate	91-08-7	< 0.2

#### **Section 4 - First Aid Measures**

#### 4.1 Description of first aid measures

**Inhalation:** Remove source(s) of contamination and move victim to fresh air. If breathing has stopped, give artificial respiration, then oxygen if needed. Contact physician immediately.

**Eye Contact:** Flush eyes with plenty of water. If irritation persists, seek medical attention.

**Skin Contact:** In case of skin contact, wash thoroughly with soap and water.

**Ingestion:** Do not induce vomiting unless instructed by a physician. Never give anything by mouth to an unconscious person.

### 4.2 Most important symptoms and effects, both acute and delayed

Eczema, asthma, lung edema.

For TDI: In sensitized individuals, sensitization reactions may be elicited by structurally similar substances. Respiratory sensitization may result in allergic, asthma-like symptoms in the lower respiratory tract including wheezing, shortness of breath and difficulty breathing, the onset of which may be delayed. Repeated inhalation of high concentrations may cause lung damage, including reduced lung function, which may be permanent.



**SDS No. 644A** 

4.3 After first aid, get appropriate in-plant, paramedic, or community medical support.

### **Section 5 - Fire-Fighting Measures**

- **5.1 Extinguishing Media:** Water Fog, Dry Chemical, and Carbon Dioxide Foam
- 5.2 Special hazards arising from the substance or mixture: None known.
- 5.3 Advice for firefighters: Use water spray to cool fire-exposed surfaces and to protect personnel. Shut off "fuel" to fire. If a leak or spill has not ignited, use water spray to disperse the vapors. Either allow fire to burn under controlled conditions or extinguish with foam or dry chemical. Try to cover liquid spills with foam. Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure demand or positive-pressure mode.

### **Section 6 - Accidental Release Measures**

- **Personal precautions, protective equipment and emergency procedures:** Only properly protected personnel should remain in the spill area; dike and contain spill. Stop or reduce discharge if it can be done safely.
- **6.2 Environmental precautions:** Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains or unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers. No special environmental precautions required.
- **Methods and material for containment and cleaning up:** Put on appropriate protective gear including NIOSH/MSHA approved self-contained breathing apparatus, rubber boots and heavy rubber gloves. Dike and contain spill; absorb or scrape up excess into suitable container for disposal; wash area with dilute ammonia solution. Stop or reduce discharge if it can be done safely.
  - Follow applicable OSHA regulations (29 CFR 1910.120) for disposal.
- **6.4** Reference to other sections: See Section 3 for list of Hazardous Ingredients; Sections 8 for Exposure Controls; and Section 13 for Disposal.

### Section 7 - Handling and Storage

- **7.1 Precautions for safe handling:** Use good general housekeeping procedures. Wash hands after use. Do not get in eyes, on skin or on clothing. Do not breathe vapors or mists. Use good personal hygiene practices.
- 7.2 Conditions for safe storage, including any incompatibilities: Keep container(s) tightly closed and properly labeled. Store in cool, dry, well ventilated place away from heat, direct sunlight, strong oxidizers and any incompatibles. Store in approved containers and protect against physical damage. Keep containers securely sealed when not in use. Indoor storage should meet OSHA standards and appropriate fire codes. Containers that have been opened must be carefully resealed to prevent leakage. Empty containers retain residue and may be dangerous. Avoid water contamination.
- **7.3 Specific end use(s):** These precautions are for room temperature handling. Other uses including elevated temperatures or aerosol/spray applications may require added precautions.

#### **Section 8 - Exposure Controls / Personal Protection**

8.1 Control parameters:

Toluene-2,6-diisocyanate 91-08-7 ACGIH TLV TWA: 0.001 ppm

STEL: 0.005 ppm



**SDS No. 644A** 

Toluene-2,4-diisocyanate 584-84-9 OSHA PEL CLV: 0.02 ppm 0.14 mg/m<sup>3</sup>

TWA: 0.005 ppm 0.04 mg/m<sup>3</sup>

STEL: 0.02 ppm 0.15 mg/m<sup>3</sup>

ACGIH TLV TWA: 0.001 ppm

STEL: 0.005 ppm

### 8.2 Exposure controls:

**Respiratory Protection:** Respiratory protection is not normally required when using this product with adequate local exhaust ventilation. Where risk assessment shows air-purifying respirators are appropriate, follow OSHA respirator regulations 29 CFR 1910.134 and European Standards EN 141, 143 and 371; wear an MSHA/NIOSH or European Standards EN 141, 143 and 371 approved respirators equipped with appropriate filter cartridges as a backup to engineering controls.

Hand Protection: Wear any liquid-tight gloves such as butyl rubber, neoprene or PVC.

**Eye Protection:** Safety glasses with side shields per OSHA eye- and face-protection regulations 29 CFR 1910.133 and European Standard EN166. Contact lenses are not eye protective devices.

Appropriate eye protection must be worn instead of, or in conjunction with contact lenses. **Other Protective Clothing/Equipment:** Additional protective clothing or equipment is not

normally required. Provide eye bath and safety shower.

**Comments:** Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics. Wash thoroughly after handling.

## **Section 9 - Physical and Chemical Properties**

### 9.1 Information on basic physical and chemical properties:

**Appearance:** Clear yellow vicous liquid **Odor/Threshold:** Sharp pungent odor

**pH:** N.A. (non-aqueous)

Melting Point/Freezing Point: N.A. Low/High Boiling Point: N.A.

Flash Point: >270°F

**Evaporation Rate:** Not available **Flammability:** f.p. at or above 200 °F

**UEL/LEL:** Not available

Vapor Pressure: None (Polymeric Resin)

Vapor Density (Air=1): >1

Specific Gravity (H2O=1, at 4 °C): 1.04

Water Solubility: Negligible Partition coefficient: Not available

Auto-ignition temperature: Not available **Decomposition temperature**: Not available

Viscosity: <5,000 centipoise % Volatile: 0% (v/v), 0% (w/w)

### Section 10 - Stability and Reactivity

- **10.1 Reactivity:** Reacts with water with formation of carbon dioxide. Risk of bursting. Reacts with alcohols, acids, alkalis, amines. Risk of exothermic reaction.
- **10.2 Chemical stability:** These products are stable at room temperature in closed containers under normal storage and handling conditions.
- **10.3 Possibility of hazardous reactions:** Risk of polymerization.
- 10.4 Conditions to avoid: Do not exceed 120 °F.
- **10.5** Incompatible materials: alcohols, acids, alkalis, amines, water
- **10.6 Hazardous decomposition products:** Thermal oxidative decomposition can produce carbon oxides, gasses/vapors, and traces of incompletely burned carbon compounds.

### **Section 11- Toxicological Information**

11.1 Information on toxicological effects:

Skin Corrosion/Irritation: no data



**SDS No. 644A** 

**Serious Eye Damage/Irritation:** no data **Respiratory/Skin Sensitization:** no data

Germ Cell Mutagenicity: no data

Carcinogenicity: toluene diisocyanate has been classified by IARC as a Group 2B (Possibly

carcinogenic to humans. NTP has listed it as a carcinogen.

Reproductive Toxicity: no data

Specific Target Organ Toxicity – Single Exposure: no data Specific Target Organ Toxicity – Repeated Exposure: no data

Aspiration Hazard: no data
Acute Toxicity: no data
Chronic Exposure: no data

Potential Health Effects - Miscellaneous: no data

## Section 12 - Ecological Information

- **12.1 Toxicity:** no data
- 12.2 Persistence and Degradability: no data
- 12.3 Bioaccumulative Potential: no data
- 12.4 Mobility in Soil: no data
- 12.5 Results of PBT and vPvB assessment: no data
- 12.6 Other Adverse Effects: no data

### **Section 13 - Disposal Considerations**

**13.1 Waste treatment methods:** Under Resource Conservation and Recovery Act (RCRA) it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste as defined in 40 CFR Part 261. Waste management should be in full compliance with federal, state and local laws. Empty containers retain product residue which may exhibit hazards of material, therefore to not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

### **Section 14 - Transport Information**

Not regulated by DOT, IATA or IMDG

- 14.1 UN number: none
- 14.2 UN proper shipping name: none
- 14.3 Transport hazard class(es): not applicable
- 14.4 Packing group: not applicable
- 14.5 Environmental hazards: none known
- 14.6 Special precautions for user: none known
- 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: not applicable



**SDS No. 644A** 

### Section 15 - Regulatory Information

15.1 Safety health and environmental regulations/legislation specific for the substance or mixture:

REACH: Regulation (EC) No 1907/2006 of The European Parliament and of The Council of December 2006 (including amendments and corrigenda as of 17 February 2016): This product complies with REACH or is not subject to regulation under REACH. The product does not contain an ingredient listed on either the Candidate List or Authorization List for Substances of Very High Concern (SVHC).

### In the United States (EPA Regulations):

**TSCA Inventory Status (40 CFR710):** All components of this formulation are listed in the TSCA Inventory. No component of this formulation has been determined to be subject to manufacturing or use restrictions under the Significant New Use Rules (SNURs).

**CERCLA Hazardous Substance** (40 CFR 302.4) listed specific per RCRA, Sec. 3001; CWA, Sec. 311 (b)(4); CWA, Sec. 307(a), CAA, Sec. 112

Chemical Name	CAS#	RQ	% Reportable Component
Toluene-2,6-diisocyanate	91-08-7	100 lbs.	<0.2
Toluene-2,4-diisocyanate	584-84-9	100 lbs	<1.0

### SARA EHS (Extremely Hazardous Substance) (40 CFR 355):

Chemical Name	CAS#	<u>RQ</u>	% by Weight
Toluene-2,6-diisocyanate	91-08-7	100 lbs.	<0.2
Toluene-2,4-diisocyanate	584-84-9	100 lbs	<1.0

These products contain the following chemicals that are subject to release reporting requirements under section 313 of SARA Title III.

Chemical Name	CAS#	RQ	% by Weight
Toluene-2,6-diisocyanate	<del>91-08-</del> 7	100 lbs.	<0.2
Toluene-2,4-diisocyanate	584-84-9	100 lbs	<1.0

SARA 311/312 Hazards: Fire, Immediate (Acute), Delayed (Chronic)

<u>California Proposition 65</u>: WARNING: This product contains chemicals known to the state of California to cause cancer.

**15.2 Chemical safety assessment:** No chemical safety assessment has been carried out for this substance/mixture by the supplier.



**SDS No. 644A** 

### 16 - Other Information

HMIS	
Н	2
F	1
R	1



Revision: 11

Date Prepared: August 16, 2017

Glossary: ACGIH-American Conference of Governmental Industrial Hygienists; ANSI-American National Standards Institute; Canadian TDG-Canadian Transportation of Dangerous Goods; CAS-Chemical Abstract Service: Chemtrec-Chemical Transportation Emergency Center (US): CHIP-Chemical Hazard Information and Packaging; DSL-Domestic Substances List; EC-Equivalent Concentration; EH40 (UK)-HSE Guidance Note EH40 Occupational Exposure Limits; EPCRA-Emergency Planning and Community Right-To-Know Act; ESL-Effects screening levels; GHS-Globally Harmonized System of Classification and Labelling of Chemicals: HMIS-Hazardous Material Information Service; IATA-International Air Transport Association; IMDG-International Maritime Dangerous Goods Code; LC-Lethal Concentration; LD-Lethal Dose; LEL-Lower Explosion Level; NFPA-National Fire Protection Association; OEL-Occupational Exposure Limit; OSHA-Occupational Safety and Health Administration, US Dept. of Labor; PEL-Permissible Exposure Limit; SARA (Title III)-Superfund Amendments and Reauthorization Act; SARA 313-Superfund Amendments and Reauthorization Act, Section 313; SCBA-Self-Contained Breathing Apparatus; STEL-Short Term Exposure Limit; TCEQ-Texas Commission on Environmental Quality: TLV-Threshold Limit Value: TSCA-Toxic Substances Control Act Public Law 94-469; TWA-Time Weighted Value; UEL-Upper Explosion Level; US DOT-US Department of Transportation; WHMIS-Workplace Hazardous Materials Information System.

**Disclaimer:** The information contained in this Safety Data Sheet (SDS) is considered accurate as of the version date. However, no warranty is expressed or implied regarding the accuracy of the data. Since the use of this product is not within the control of Smooth-On Inc., it is the user's obligation to determine the suitability of the product for its intended application and assumes all risk and liability for its safe use.

This SDS is prepared to comply with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) as prescribed by the United States (US) Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200), the Canadian Workplace Hazardous Materials Information System (WHMIS), and European Union Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 (REACH).

Classifications of the chemical in accordance with 29 CFR 1910.1200, signal word, hazard and precautionary statement(s), symbol(s) and other information are based on listed concentration of each hazardous ingredient. Unlisted ingredients are not "hazardous" per the OSHA Hazard Communication Standard (29 CFR 1910.1200), WHMIS and EC No 1907/2006 and are considered trade secrets under US Federal Law (29 CFR and 40 CFR), Canadian Law (Health Canada Legislation), and European Union Directives.



**SDS No. 419B** 

#### Section 1 - Identification

1.1 Product Identifier: Part B for Brush-On® 40, 50, 60; Econ® 60 and 80; EZ-Spray®

Plastic; Foam-iT! 4, 4 Black, 5, 8; Formlastic<sup>™</sup> 48, 60; Plasti-Paste<sup>®</sup> and Plasti-Paste<sup>®</sup> II; PMC<sup>®</sup> 121-30 Dry and Wet, PMC<sup>®</sup> 744, 770, 844; Renew<sup>™</sup> UR-40, UR-60; ReoFlex<sup>®</sup> 20 Dry, 30 Dry and Wet, 40 Dry and Wet, 50 Dry and Wet, 60 Dry and Wet; Shell Shock<sup>®</sup> Fast and Slow; Smooth-Cast<sup>®</sup> 305, 310, 321, 322, 385; Task<sup>®</sup> 4, 5, 6, 18; Urethane 4400; VytaFlex<sup>®</sup> 10, 20, 30, 40, 50, 60

Part A for TerraCon® 55; Urethane 4040

**1.2 General Use:** Polyurethane Elastomer

**1.3 Manufacturer:** Smooth-On, Inc.,

5600 Lower Macungie Rd., Macungie, PA 18062 Phone (610) 252-5800, sds@smooth-on.com

1.4 Emergency Contact: Chem-Tel Domestic: 800-255-3924 International: 813-248-0585

### Section 2 - Hazard(s) Identification

#### 2.1 Classification of the substance or mixture

Not a hazardous substance or mixture according to United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200), the Canadian Workplace Hazardous Materials Information System (WHMIS) and Regulation (EC) No 1272/2008 and subsequent amendments.

#### 2.2 GHS Label elements, including precautionary statements

Pictogram(s): none Signal word: none

#### **General Precautions:**

P101: If medical advice is needed, have product container or label at hand.

P102: Keep out of reach of children.

P103: Read label before use.

Hazards not otherwise classified (HNOC) or not covered by GHS – This product contains a chemical known to be hazardous according to California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65). (See also Section 3 and 15)

### Section 3 - Composition / Information on Ingredients

#### 3.1 Substances

No ingredients are hazardous according to Regulation 2012 OSHA Hazard Communication Standard 29 CFR 1910.1200 criteria.

#### **Section 4 - First Aid Measures**

### 4.1 Description of first aid measures

**Inhalation:** Remove source(s) of contamination and move victim to fresh air. If breathing has stopped, give artificial respiration, then oxygen if needed. Contact physician immediately.



**SDS No. 419B** 

**Eye Contact:** Flush eyes with plenty of water. If irritation persists, seek medical attention.

Skin Contact: In case of skin contact, wash thoroughly with soap and water.

**Ingestion:** Do not induce vomiting unless instructed by a physician. Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 After first aid, get appropriate in-plant, paramedic, or community medical support.

### **Section 5 - Fire-Fighting Measures**

- **5.1 Extinguishing Media:** Water Fog, Dry Chemical, and Carbon Dioxide Foam
- 5.2 Special hazards arising from the substance or mixture: None known.
- 5.3 Advice for firefighters: Use water spray to cool fire-exposed surfaces and to protect personnel. Shut off "fuel" to fire. If a leak or spill has not ignited, use water spray to disperse the vapors. Either allow fire to burn under controlled conditions or extinguish with foam or dry chemical. Try to cover liquid spills with foam. Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure demand or positive-pressure mode.

#### **Section 6 - Accidental Release Measures**

- **Personal precautions, protective equipment and emergency procedures:** Only properly protected personnel should remain in the spill area; dike and contain spill. Stop or reduce discharge if it can be done safely.
- **6.2 Environmental precautions:** No special environmental precautions required.
- **6.3 Methods and material for containment and cleaning up:** absorb or scrape up excess into suitable container for disposal; wash area with dilute ammonia solution
- **6.4** Reference to other sections: if appropriate Sections 8 and 13 shall be referred to.

### Section 7 - Handling and Storage

- **7.1 Precautions for safe handling:** Use good general housekeeping practices. Wash hands after use.
- 7.2 Conditions for safe storage, including any incompatibilities: Keep container(s) tightly closed and properly labeled. Store in cool, dry, well ventilated place away from heat, direct sunlight, strong oxidizers and any incompatibles. Store in approved containers and protect against physical damage. Keep containers securely sealed when not in use. Indoor storage should meet OSHA standards and appropriate fire codes. Containers that have been opened must be carefully resealed to prevent leakage. Empty containers retain residue and may be dangerous. Avoid water contamination.
- **7.3 Specific end use(s):** These precautions are for room temperature handling. Other uses including elevated temperatures or aerosol/spray applications may require added precautions.

### Section 8 - Exposure Controls / Personal Protection

- **8.1 Control parameters:** none defined
- 8.2 Exposure controls:

**Respiratory Protection:** Should a respirator be needed, follow OSHA respirator regulations 29 CFR 1910.134 and European Standards EN 141, 143 and 371; wear an MSHA/NIOSH or European Standards EN 141, 143 and 371 approved respirators equipped with organic vapor cartridges.

Hand Protection: Wear any liquid-tight gloves such as butyl rubber, neoprene or PVC.



**SDS No. 419B** 

**Eye Protection:** Safety glasses with side shields per OSHA eye- and face-protection regulations 29 CFR 1910.133 and European Standard EN166. Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses. **Other Protective Clothing/Equipment:** Additional protective clothing or equipment is not normally required. Provide eye bath and safety shower.

**Comments:** Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics. Wash thoroughly after handling.

### **Section 9 - Physical and Chemical Properties**

### 9.1 Information on basic physical and chemical properties:

Appearance: clear to amber liquid Vapor Pressure: None (Polymeric Resin)

Odor/Threshold: Mild odor Vapor Density (Air=1): >1

pH: N.A. (non-aqueous) Specific Gravity (H<sub>2</sub>O=1, at 4 °C): 1.05-1.25

Melting Point/Freezing Point: N.A.

Water Solubility: Insoluble Partition coefficient: Not as

Low/High Boiling Point: N.A. Partition coefficient: Not available

Flash Point: >300 °F Auto-ignition temperature: Not available

Evaporation Rate: Not available

Decomposition temperature: Not available

### Section 10 - Stability and Reactivity

- **10.1 Reactivity:** No hazardous reactions if stored and handled as prescribed/indicated., No corrosive effect on metal. Not fire propagating.
- **10.2 Chemical stability:** These products are stable at room temperature in closed containers under normal storage and handling conditions.
- 10.3 Possibility of hazardous reactions: Hazardous polymerization cannot occur.
- **10.4 Conditions to avoid:** none known
- **10.5 Incompatible materials:** strong bases and acids
- **10.6 Hazardous decomposition products:** Thermal oxidative decomposition can produce carbon oxides, gasses/vapors, and traces of incompletely burned carbon compounds.

### Section 11- Toxicological Information

### 11.1 Information on toxicological effects:

Skin Corrosion/Irritation: no data
Serious Eye Damage/Irritation: no data
Respiratory/Skin Sensitization: no data
Germ Cell Mutagenicity: no data

Carcinogenicity: No component of these products present at levels greater than or equal to 0.1% is

identified as a carcinogen or potential carcinogen by IARC, ACGIH or NTP.

Reproductive Toxicity: no data

Specific Target Organ Toxicity – Single Exposure: no data Specific Target Organ Toxicity – Repeated Exposure: no data

**Aspiration Hazard:** no data **Acute Toxicity:** (Calculated)

LD50 Oral, rat: >37,000 mg/kg LC50 Inhalation, rat (4 h): >16.3 mg/l



**SDS No. 419B** 

LD50 Dermal, rabbit: >11,700 mg/kg

Chronic Exposure: no data

Potential Health Effects - Miscellaneous: no data

### **Section 12 - Ecological Information**

12.1 Toxicity:

LC50 (semi-static, 96 h): > 380 mg/l, Danio rerio EC50 (static, 48 h): >270 mg/l, Daphnia magna

EC50 (static, 72 h): >330 mg/l, Desmodesmus subspicatus

- 12.2 Persistence and Degradability: no data
- 12.3 Bioaccumulative Potential: no data
- 12.4 Mobility in Soil: no data
- 12.5 Results of PBT and vPvB assessment: no data
- 12.6 Other Adverse Effects: no data

### **Section 13 - Disposal Considerations**

13.1 Waste treatment methods: Under RCRA it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws. Empty containers retain product residue which may exhibit hazards of material, therefore to not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

### **Section 14 - Transport Information**

Not regulated by DOT, IATA or IMDG

- 14.1 UN number: none
- 14.2 UN proper shipping name: none
- 14.3 Transport hazard class(es): not applicable
- 14.4 Packing group: not applicable
- **14.5** Environmental hazards: none known
- 14.6 Special precautions for user: none known
- 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: not

applicable

### **Section 15 - Regulatory Information**

15.1 Safety health and environmental regulations/legislation specific for the substance or mixture:

REACH: Regulation (EC) No 1907/2006 of The European Parliament and of The Council of December 2006 (including amendments and corrigenda as of 17 February 2016): This product complies with REACH or is not subject to regulation under REACH. The product does not contain an ingredient listed on either the Candidate List or Authorization List for Substances of Very High Concern (SVHC).

### In the United States (EPA Regulations):

**TSCA Inventory Status (40 CFR710):** All components of this formulation are listed in the TSCA Inventory.



**SDS No. 419B** 

**SARA 302 Components:** No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313 Components:** No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 313.

SARA 311/312 Hazards: none

<u>California Proposition 65</u>: WARNING: This product contains chemicals known to the state of California to cause cancer.

**15.2 Chemical safety assessment:** No chemical safety assessment has been carried out for this substance/mixture by the supplier.

#### 16 - Other Information

HMIS	
Н	1
F	1
R	0



Revision: 10

Date Prepared: August 16, 2017

Glossary: ACGIH-American Conference of Governmental Industrial Hygienists; ANSI-American National Standards Institute: Canadian TDG-Canadian Transportation of Dangerous Goods; CAS-Chemical Abstract Service; Chemtrec-Chemical Transportation Emergency Center (US); CHIP-Chemical Hazard Information and Packaging; DSL-Domestic Substances List; EC-Equivalent Concentration; EH40 (UK)-HSE Guidance Note EH40 Occupational Exposure Limits; EPCRA-Emergency Planning and Community Right-To-Know Act; ESL-Effects screening levels; GHS-Globally Harmonized System of Classification and Labelling of Chemicals; HMIS-Hazardous Material Information Service: IATA-International Air Transport Association: IMDG-International Maritime Dangerous Goods Code; LC-Lethal Concentration; LD-Lethal Dose; LEL-Lower Explosion Level; NFPA-National Fire Protection Association; OEL-Occupational Exposure Limit; OSHA-Occupational Safety and Health Administration, US Dept. of Labor; PEL-Permissible Exposure Limit; SARA (Title III)-Superfund Amendments and Reauthorization Act; SARA 313-Superfund Amendments and Reauthorization Act, Section 313; SCBA-Self-Contained Breathing Apparatus; STEL-Short Term Exposure Limit; TCEQ-Texas Commission on Environmental Quality; TLV-Threshold Limit Value; TSCA-Toxic Substances Control Act Public Law 94-469; TWA-Time Weighted Value; UEL-Upper Explosion Level; US DOT-US Department of Transportation; WHMIS-Workplace Hazardous Materials Information System.

**Disclaimer:** The information contained in this Safety Data Sheet (SDS) is considered accurate as of the version date. However, no warranty is expressed or implied regarding the accuracy of the data. Since the use of this product is not within the control of Smooth-On Inc., it is the user's obligation to determine the suitability of the product for its intended application and assumes all risk and liability for its safe use.

This SDS is prepared to comply with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) as prescribed by the United States (US) Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200), the Canadian





**SDS No. 419B** 

Workplace Hazardous Materials Information System (WHMIS), and European Union Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 (REACH).

Classifications of the chemical in accordance with 29 CFR 1910.1200, signal word, hazard and precautionary statement(s), symbol(s) and other information are based on listed concentration of each hazardous ingredient. Unlisted ingredients are not "hazardous" per the OSHA Hazard Communication Standard (29 CFR 1910.1200), WHMIS and EC No 1907/2006 and are considered trade secrets under US Federal Law (29 CFR and 40 CFR), Canadian Law (Health Canada Legislation), and European Union Directives.