

Safety Data Sheet

SDS No. 32B

Section 1 - Chemical Product and Company Identification

Product/Chemical Name: EpoxAmite® 103 Slow Part B

General Use: Epoxy Curing Resin Manufacturer: Smooth-On, Inc.,

> 5600 Lower Macungie Rd., Macungie, PA 18062 Phone (610) 252-5800, FAX (610) 252-6200

Emergency Contact: Chem-Tel

Domestic: 800-255-3924 International: 813-248-0585

Section 2 - Hazards Identification

Classification of the substance or mixture

Acute toxicity, oral – Category 4 Acute toxicity, inhalation - Category 4 Skin corrosion/irritation - Category 2A Eye damage/irritation - Category 2A Acute aquatic – Category 3

Pictogram(s):

Signal Word: Danger

GHS Label elements, including precautionary statements				
Health	H302	Harmful if swallowed		
Hazards:				
	H314	Causes severe skin burns and eye damage		
	H319	Causes serious eye irritation		
	H332	Harmful if inhaled		
	H402	Harmful to aquatic life.		
General Precautions:	P101	If medical advice is needed, have product container or label at hand.		
	P102	Keep out of reach of children.		
	P103	Read label before use.		
Prevention Precautions:	P264	Wash skin thoroughly after handling.		
	P271	Use only outdoors or in a well-ventilated area.		
Response Precautions:	P301 + P312	IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.		
	P302 + P352	IF ON SKIN: Wash with plenty of soap and water.		
	P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.		
	P305 + P351 +	IF IN EYES: Rinse cautiously with water for several minutes.		
	P338	Remove contact lenses, if present and easy to do. Continue rinsing.		

P332 + P313 If skin irritation occurs: Get medical advice/attention.

P337 + P313 If eye irritation persists: Get medical advice/attention.

Storage P405 Store locked up.

Precautions:

Disposal P501 Dispose of contents/container according to local, state and

Precautions: federal laws.

Hazards not otherwise classified (HNOC) or not covered by GHS - none

Section 3 - Composition / Information on Ingredients

The following ingredients are hazardous according to OSHA criteria:

	U	
CAS	Component	Concentration
1761-71-3	Methylenebiscycloheanamine, 4,4'-	65% - 70%
39423-51-3	Trimethylolpropane polyoxypropylene triamine	18% - 30%

Section 4 - First Aid Measures

Inhalation: Remove source(s) of contamination and move victim to fresh air. If breathing has stopped, give artificial respiration, then oxygen if needed. Contact physician immediately. **Eye Contact:** Flush eyes with plenty of water. If irritation persists, seek medical attention.

Skin Contact: In case of skin contact, wash thoroughly with soap and water.

Ingestion: Do not induce vomiting unless instructed by a physician. Never give anything by mouth to an unconscious person.

After first aid, get appropriate in-plant, paramedic, or community medical support.

Section 5 - Fire-Fighting Measures

Flammable Classification: Non-Flammable

Extinguishing Media: Water Fog, Dry Chemical, and Carbon Dioxide Foam

Unusual Fire or Explosion Hazards: None known.

Fire-Fighting Instructions: Use water spray to cool fire-exposed surfaces and to protect personnel. Shut off "fuel" to fire. If a leak or spill has not ignited, use water spray to disperse the vapors. Either allow fire to burn under controlled conditions or extinguish with foam or dry chemical. Try to cover liquid spills with foam.

Further information: Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure demand or positive-pressure mode.

Section 6 - Accidental Release Measures

Spill /Leak procedures:

Only properly protected personnel should remain in the spill area; dike and contain spill; absorb or scrape up excess into suitable container for disposal; wash area with dilute ammonia solution. Stop or reduce discharge if it can be done safely.

Environmental precautions:

Prevent further leakage or spillage.

Section 7 - Handling and Storage

Handling Precautions: Ensure good ventilation at the workplace. Use good general housekeeping procedures. Wash hands after use.

Storage Requirements: Keep container(s) tightly closed and properly labeled. Store in cool, dry, well ventilated place away from heat, direct sunlight, strong oxidizers and any incompatibles. Store in approved containers and protect against physical damage. Keep containers securely sealed when not in use. Indoor storage should meet OSHA standards and appropriate fire codes. Containers that have been opened must be carefully resealed to prevent leakage. Empty containers retain residue and may be dangerous. Avoid water contamination.

Section 8 - Exposure Controls / Personal Protection

Respiratory Protection: Respiratory protection is not normally required when using this product with adequate ventilation. Should a respirator be needed, follow OSHA respirator regulations 29 CFR 1910.134 and European Standards EN 141, 143 and 371; wear an MSHA/NIOSH or European Standards EN 141, 143 and 371 approved respirators equipped with organic vapor cartridges.

Hand Protection: Wear chemical resistant liquid-tight gloves such as butyl rubber, neoprene or PVC.

Eye Protection: Safety glasses with side shields per OSHA eye- and face-protection regulations 29 CFR 1910.133 and European Standard EN166. Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses.

Other Protective Clothing/Equipment: Additional protective clothing or equipment is not normally required. Provide eye bath and safety shower.

Comments: Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics. Wash thoroughly after handling.

Section 9 - Physical and Chemical Properties

Appearance: amber liquid

Odor/Threshold: Mild ammonia odor

pH: NA (non-aqueous)

Melting Point/Freezing Point: N.A. Low/High Boiling Point: Not available

Flash Point: 347 °F

Evaporation Rate: Not available **Flammability:** f.p. at or above 200 °F

UEL/LEL: Not available

Vapor Pressure: < 1.0 mmHg @ 70 °F

Vapor Density (Air=1): >1

Specific Gravity (H2O=1, at 4 °C): 0.96

Water Solubility: Not available Partition coefficient: Not available

Auto-ignition temperature: Not available **Decomposition temperature:** Not available

Viscosity: Not available % Volatile: Not available

Section 10 - Stability and Reactivity

Stability: These products are stable at room temperature in closed containers under normal storage and handling conditions.

Polymerization: Hazardous polymerization cannot occur. **Chemical Incompatibilities:** Strong bases, and acids.

Hazardous Decomposition Products: Thermal oxidative decomposition can produce carbon oxides and traces of incompletely burned carbon compounds.

Section 11- Toxicological Information

Skin Corrosion/Irritation: severe skin irritation **Serious Eye Damage/Irritation:** severe eye irritation

Respiratory/Skin Sensitization: no data

Germ Cell Mutagenicity: not mutagenic in AMES Test

Carcinogenicity: no data

Reproductive Toxicity: no data

Specific Target Organ Toxicity – Single Exposure: no data
Specific Target Organ Toxicity – Repeated Exposure: no data

Aspiration Hazard: no data
Acute Toxicity: no data
Chronic Exposure: no data

Potential Health Effects - Miscellaneous: no data

Section 12 - Ecological Information

Toxicity: no data

Persistence and Degradability: no data Bioaccumulative Potential: no data

Mobility in Soil: no data

Other Adverse Effects: no data

Section 13 - Disposal Considerations

Disposal: Under RCRA it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws.

Empty containers retain product residue which may exhibit hazards of material, therefore to not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

Section 14 - Transport Information

DOT IATA IMDG

Proper Shipping Name:
Amines, liquid, corrosive, n.o.s.

(4,4'-methylene

biscyclohexanamine and polyoxypropylene triamine)

UN: 2735 HC: 8 PG: II Label: Corrosive Proper Shipping Name: Amines, liquid, corrosive, n.o.s. (4,4'-methylene

biscyclohexanamine and polyoxypropylene triamine)

UN: 2735 HC: 8 PG: II Label: Corrosive **Proper Shipping Name:**

Amines, liquid, corrosive, n.o.s.

(4,4'-methylene

biscyclohexanamine and polyoxypropylene triamine)

UN: 2735 HC: 8 PG: II Label: Corrosive

Section 15 - Regulatory Information

TSCA Inventory Status (40 CFR710): All components of this formulation are listed in the TSCA Inventory.

<u>California Proposition 65</u>: This product does not intentionally contain any chemicals which have been identified by the state of California to cause cancer, birth defects or other reproductive harm.

16 - Other Information

HMIS		
Η	3	
F	1	
R	0	



NFPA

Revision: 5

Date Prepared: May 6, 2015

Glossary: ACGIH-American Conference of Governmental Industrial Hygienists; ANSI-American National Standards Institute: Canadian TDG-Canadian Transportation of Dangerous Goods: CAS-Chemical Abstract Service; Chemtrec-Chemical Transportation Emergency Center (US); CHIP-Chemical Hazard Information and Packaging; DSL-Domestic Substances List; EC-Equivalent Concentration; EH40 (UK)-HSE Guidance Note EH40 Occupational Exposure Limits; EPCRA-Emergency Planning and Community Right-To-Know Act; ESL-Effects screening levels; GHS-Globally Harmonized System of Classification and Labelling of Chemicals; HMIS-Hazardous Material Information Service; IATA-International Air Transport Association; IMDG-International Maritime Dangerous Goods Code; LC-Lethal Concentration; LD-Lethal Dose; LEL-Lower Explosion Level; NFPA-National Fire Protection Association; OEL-Occupational Exposure Limit; OSHA-Occupational Safety and Health Administration, US Dept. of Labor; PEL-Permissible Exposure Limit: SARA (Title III)-Superfund Amendments and Reauthorization Act; SARA 313-Superfund Amendments and Reauthorization Act, Section 313; SCBA-Self-Contained Breathing Apparatus; STEL-Short Term Exposure Limit; TCEQ-Texas Commission on Environmental Quality; TLV-Threshold Limit Value; TSCA-Toxic Substances Control Act Public Law 94-469; TWA-Time Weighted Value; UEL-Upper Explosion Level; US DOT-US Department of Transportation; WHMIS-Workplace Hazardous Materials Information System.

Disclaimer: The information contained in this Safety Data Sheet (SDS) is considered accurate as of the version date. However, no warranty is expressed or implied regarding the accuracy of the data. Since the use of this product is not within the control of Smooth-On Inc., it is the user's obligation to determine the suitability of the product for its intended application and assumes all risk and liability for its safe use.

This SDS is prepared to comply with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) as prescribed by the United States (US) Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200), the Canadian Workplace Hazardous Materials Information System (WHMIS), and European Union Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 (REACH).

Classifications of the chemical in accordance with 29 CFR 1910.1200, signal word, hazard and precautionary statement(s), symbol(s) and other information are based on listed concentration of each hazardous ingredient. Unlisted ingredients are not "hazardous" per the OSHA Hazard Communication Standard (29 CFR 1910.1200), WHMIS and EC No 1907/2006 and are considered trade secrets under US Federal Law (29 CFR and 40 CFR), Canadian Law (Health Canada Legislation), and European Union Directives.