

# Ease Release™ 2831

**Wax-Based Non-Silicone Release Agent**



www.smooth-on.com

## PRODUCT OVERVIEW

**Ease Release™ 2831** is a wax-based non-silicone release agent. It has proven to be effective when used to release polyurethane foams elastomers. **Ease Release™ 2831** works with aluminum, steel, and elastomeric mold construction.

### Features:

- Excellent Release
- Non-Silicone
- Contains no chlorinated or CFC solvents
- Low wax build-up

### Provides:

- Increased productivity
- Excellent cleanability
- Low environmental hazards
- Low mold maintenance

## PROCESSING RECOMMENDATIONS

**PREPARATION...Safety** - Use in a properly ventilated area ("room size" ventilation). Wear safety glasses, long sleeves and rubber gloves to minimize contamination risk. Skin contact may cause dryness.

Store and use material at room temperature (73°F/23°C). This product has a limited shelf life and should be used as soon as possible.

## APPLYING & FINISHING...

### SHAKE WELL BEFORE USING

**Applying** - Apply a coat of Ease Release™ 2831 with a spray or brush, and allow to dry. Rub Ease Release™ 2831 into mold surface with a clean cloth. Repeat two or three times to seal the mold surface. Start molding and reapply a light coat of Ease Release™ 2831 after each molding cycle.

**Finishing** - Thorough cleaning of the molded parts is recommended prior to bonding or any other post mold finishing.

## PRODUCT CHARACTERISTICS

Product Specifications	
Appearance	Hazy liquid
Solids	6 - 7 %
Application	Spray
Viscosity	Medium

### Safety First!

The Material Safety Data Sheet (MSDS) for this or any Smooth-On product should be read prior to use and is available upon request from Smooth-On. All Smooth-On products are safe to use if directions are read and followed carefully.

#### Keep Out of Reach of Children

**IMPORTANT** - The information contained in this bulletin is considered accurate. However, no warranty is expressed or implied regarding the accuracy of the data, the results to be obtained from the use thereof, or that any such use will not infringe upon a patent. User shall determine the suitability of the product for the intended application and assume all risk and liability whatsoever in connection therewith.



**Call Us Anytime With Questions About Your Application**

Toll-free: (800) 381-1733 Fax: (610) 252-6200

The new [www.smooth-on.com](http://www.smooth-on.com) is loaded with information about mold making, casting and more.